

### **Amendments to the Claims**

1. (currently amended) A method for controlling congestion in a communications network, including:
  - receiving congestion feedback data relating to said network;
  - adjusting ~~both~~ at least one of a window limit and a rate limit based on said congestion feedback data; and
  - injecting data packets onto said network according to said window limit and said rate limit, wherein the window limit controls a number of packets in transit between source and destination nodes and the rate limit controls a rate at which the source node injects packets into the communications network.
2. (original) A method according to claim 1, wherein said adjusting includes:
  - decreasing said rate limit and said window limit if said network is determined to be congested based on said congestion feedback data.
3. (original) A method according to claim 1, wherein said adjusting includes:
  - increasing, based on a limiting factor, at least one of said rate limit and said window limit if said network is determined not to be congested based on said congestion feedback data.
4. (currently amended) A method according to claim 3, wherein said limiting factor is determined based on whether ~~a~~ the transmission of a data packet was most recently limited by at least one of said rate limit and said window limit.
5. (currently amended) A method according to claim 4, wherein ~~only~~ said rate limit is increased if said limiting factor is determined by said rate limit.
6. (currently amended) A method according to claim 4, wherein ~~only~~ said window limit is increased if said limiting factor is determined by said window limit.

7. (original) A method according to claim 4, wherein both said rate limit and said window limit is increased if said limiting factor is determined by both said rate limit and said window limit.

8. (original) A method according to claim 4, wherein said limiting factor is a value between a predetermined high threshold and a predetermined low threshold.

9. (currently amended) A method according to claim 4, wherein said determining of said limiting factor includes increasing or decreasing said limiting factor by an amount corresponding to a ~~the~~ size of the data packet for which injection was limited.

10. (original) A method according to claim 9, wherein said limiting factor is increased by said amount if the transmission of a data packet was limited by said window limit.

11. (original) A method according to claim 9, wherein said limiting factor is decreased by said amount if the transmission of a data packet was limited by said rate limit.

12. (original) A method according to claim 1, wherein said adjusting is performed by an Additive Increase Multiplicative Decrease response process.

13. (currently amended) A system for controlling congestion in a communications network, including:

a congestion control module adapted to adjust at least one of a window limit and a rate limit based on congestion feedback data relating to said network, and to limit injection of packets into said network according to both said window limit and said rate limit, wherein the window limit controls a number of packets in transit between source and destination nodes and the rate limit controls a rate at which the source node injects packets into the communications network.

14. (original) A system according to claim 13, wherein said congestion control module is adapted to decrease said rate limit and said window limit if said network is determined to

be congested based on said congestion feedback data.

15. (original) A system according to claim 13, wherein said congestion control module is adapted to increase, based on a limiting factor, at least one of said rate limit and said window limit if said network is determined not to be congested based on said congestion feedback data.

16. (currently amended) A system according to claim 15, further including means for determining said limiting factor based on whether a ~~the~~ transmission of a data packet was most recently limited by at least one of said rate limit and said window limit.

17. (currently amended) A system for controlling congestion in a communications network, comprising:

means for receiving congestion feedback data relating to said network;

means for determining which of a window limit and a rate limit are causing congestion in the network;

means for adjusting at least one of the ~~a~~ window limit and the ~~a~~ rate limit based on said congestion feedback data; and

means for injecting data packets onto said network according to both said window limit and said rate limit.

18. (original) A system according to claim 17, wherein said means for adjusting includes:

means for decreasing said rate limit and said window limit if said network is determined to be congested based on said congestion feedback data.

19. (original) A system according to claim 17, wherein said means for adjusting includes:

means for increasing, based on a limiting factor, at least one of said rate limit and said window limit if said network is determined not to be congested based on said congestion feedback data.

20. (currently amended) A system according to claim 19, wherein said limiting factor is determined based on whether a~~the~~ transmission of a data packet was most recently limited by at least one of said rate limit and said window limit.

21. – 24. (canceled)